



Stainless steel cabinet construction

Stainless steel interior and exterior (galvanized steel back & bottom).



Temperature range between 33°F ~ 39°F

Air guard on rear wall ensures proper air circulation and cooling.



Hydrocarbon refrigerants (R-290)

Increases energy HFC refrigerants. It is safer for the environment and does not cause ozone depletion.





Cabinet Dimensions (inches/mm)

L D H 67" 36 1/2" 42" 1702 mm 929 mm 1066 mm

Weight (lbs/kg)

Net Weight 412 lbs 186 kg Ship Weight 441 lbs 200 kg










Cabinet construction

- Cyclopentane Insulation Contains no hydro-fluorocarbons (HFCs) and is environmentally friendly.
- Epoxy coated wire shelves with adjustable shelving height.
- Drop-in section: Fans force cold air into this enclosed area keeping stred food items consistently cold
- Insulated pan cover with a stainless steel divider which prevents food spillage into the storage area beneath
- Standard 1/6 / 4" food pans are provided. Unit accommodates 6" deep pans
- Side rail cutting board bracket with 9 ½" deep, 1/2" thick cutting board included
- Four 4" Diameter swivel casters with front brakes standard.


Refrigeration

- Self-contained system, rear mounted compressor.
- Electrodeposition coated evaporator increases performance by maintaining the heat transfer rates over the life of the evaporator and reducing potential corrosion.
- Innovative hot gas frame heating system reduces condensation and increases energy.


Front view



Side view



Top view





- This product may exprose you to chemicals including Diisononyl Phthalate(DINP), which is known to the State of California to cause cancer. For more information go to www.P65War nings.ca.gov.
- www.roswa ningstagov.

 Ce produit peut vous exposer á des agents chimiques incluant le Diisononyl

 Phthalate(DINP), reconnu par l'Esat de Californie comme causant le cancer, Pour de plus

 amples renseignements, consulter le site www.P65Warnings.ca.gov.

Doors

- · Self-closing doors
- Durable door gasket with easy replacement.
- Lifetime guaranteed heavy duty all metal door handles. (Ni-Cr Plated)
- Door designed to open easily.

Design & Features

- Self-diagnostic digital temperature control & monitor system.
- · Digital display allows for easy monitoring.
- Digital controls include automatic evaporator fan motor delay
- Rounded corner design gives a stylish appearance and reduces chances of injury.
- Visual and audible door open alarm, alarm sounds when doors are not completely closed to protect against food spoilage

Optional Features & Accessories

- 2.5" diameter casters available.
- 6" adjustable legs available.
- · Additional shelves are available.
- Drawer odels available
- 6" pans available

4 Drawer Capacity 20.2 Cu.Ft. N/A **Shelves** Refrigerant R-290 **Temperature** 33°F ~ 39°F Range Easy Sliding Maintenance Condensing Unit 9.8 ft long (3m) flexible three Connection wire cord with modeled plug HP 3/8 Voltage 115V/60Hz **Amps** 3.5 **NEMA** Config. NEMA 5-15



Blue Air has right to change specifications without further notice.





